

## 160 Zone paging station AL-10R

### Features:

- ▶ Paging up to 16pcs of AL10P at 160 zones
- ▶ Long distance at 1KM
- ▶ Built-in pleasant chime
- ▶ High resolution LED showing the address of AL-10P paging to
- ▶ With high sensitivity gooseneck microphone and line in
- ▶ Up to 4pcs of AL-10R for the system
- ▶ Automatic mute function
- ▶ All call function

Flexible with long distance audio transmission!



SPECIFICATIONS	AL-10R
Input	Gooseneck mic: 600 ohms, 5mV, unbalanced, XLR Line in: 10k ohms, 775mV, unbalanced, RCA jack Line out: bigger than 775mV,(0dB) unbalanced
Control zones	Channel 1 to 10
Frequency Response	MIC:100Hz – 10kHz (+/- 3dB); Line: 20Hz – 15kHz
S/N Ratio	Better than 70dB
THD	Less than 0.1% at 1kHz
Power consumption	5-10W
Power Requirements	220-240V AC, 50/60 Hz
Dimensions	80(H) x 75(W) x 205(D) mm

## 10-channel paging selector AL-10P

### Features:

- ▶ Paging up to 10 speaker zones
- ▶ With 10 try contact in and out
- ▶ Built-in pleasant chime
- ▶ With 1 mic, 2 aux and 4 remote paging microphone inputs
- ▶ 4 priority levels MIC1 highest priority to EMC MIC, remote paging MIC and aux as last
- ▶ LED indicator for all the zones



SPECIFICATIONS	AL-10P
MIC Input	600 ohm 5mv, unbalance
Line input	10 K ohm, bigger or equals to 220mv unbalance
Line output	Bigger than 775mV at 0dB, Unbalance
Freq. response	MIC 100Hz-15KHz; Line 60Hz-15KHz at +/- 3dB
THD	Less than 0.01% at 1KHz
S/N Ratio	Bigger than 70dB
Protection	AC Fuse: 0.5A
Mute attenuation	Line 1 and MIC mute line 2 at 0-30dB
Power Requirements	220-240V AC, 50/60 Hz
Dimensions	89(H) x 483(W) x 366(D) mm
Built-in Dimensions	2 U rack 19 inch
Net Weight	6.4kg