

## High Performance 2 way speaker with crossover

## Features:

- ▶ 2-way ABS in ceiling speaker at high performance
- ▶ With kevlar driver and 2 tweeters
- ▶ With crossover to produce clear yet powerful sound
- ▶ Good for high demand audio environment







MODEL	CP-650L
Output Power	50W
SPL (1W/1M)	89dB
Frequency Range	60hz to 20khz
LF	6.5 inch glass fiber cone, rubber edge
HF	20vc silk dome*2pcs
Enclosure Material	ABS
Impedance	16 ohm
Size	dia 235mm*160mm
hole cut size	205mm
Weight	1.9kg
Finish	White

## High Performance 2 way speaker with crossover

## Features:

- ▶ 2-way ABS in ceiling speaker at high performance
- ▶ With 2 tweeters
- ▶ With crossover to produce clear yet powerful sound
- ▶ Good for high demand audio environment







MODEL	CP-880L
Program Power	80W
SPL (1W/1M)	87dB
Frequency Range	60hz to 20khz
LF	8 inch poly Cone, rubber surround
HF	25inch silk soft dome*2
Connector	Standard pressed
Enclosure Material	ABS
Impedance	8 ohm
Size	dia 280mm*200mm
hole cut size	248mm
Weight	2.6kg
Finish	White