




High Performance 2-way ceiling speaker



CR-620LT / CR-620L

- ▶ Easy and fast installation
- ▶ Colorful Poly woofer produces smooth and natural HiFi sound
- ▶ Designed for optimal performance in a wide variety of commercial applications



CR-620LMT/CR-620LM/CR-830LMT/CR-830LM

- ▶ Elegant Rimless design
- ▶ Easy and fast installation
- ▶ Colorful Poly woofer produces smooth and natural HiFi sound
- ▶ Designed for optimal performance in a wide variety of commercial applications



Model Number with "M" means Rimless version; with "T" means 100V line transformer version

Model	CR-620LT	CR-620L	CR-620LMT	CR-620LM	CR-830LMT	CR-830LM
Power at 100V	15W /7.5W	/	15W /7.5W	/	30W /15W /7.5W	/
Recommended Amplifier Power	/	15W to 125W	/	15W to 125W	/	20W to 125W
Power Peak	60W at 8 ohm	60W at 8 ohm	60W at 8 ohm	60W at 8 ohm	120W at 8 ohm	120W at 8 ohm
SPL(1W/1M)	89dB	89dB	89dB	89dB	89dB	89dB
Max SPL@ 1M	101dB	101dB	101dB	101dB	104dB	104dB
Freq. Response	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz	50Hz-20KHz	50Hz-20KHz
Cutout Size	Dia 170	Dia 170	Dia 170	Dia 170	Dia 210mm	Dia 210mm
Installation	Inceiling	Inceiling	Inceiling	Inceiling	Inceiling	Inceiling
Enclosure Material	ABS	ABS	ABS	ABS	ABS	ABS
Weight	1.0KG	0.8KG	1.0KG	0.8KG	1.25KG	0.9KG
Finish	White	White	White	White	White	White
Product Size	Dia186.5x95mm(H)	Dia186.5x85mm(H)	Dia 187x87mm(H)	Dia 187x80mm(H)	Dia 235x104mm(H)	Dia 235x93mm(H)
Speakers	1" x1 (TREBLE) 6"x1(BASS)	1" x1 (TREBLE) 6"x1(BASS)	1" x1 (TREBLE) 6"x1(BASS)	1" x1 (TREBLE) 6"x1(BASS)	1" x1 (TREBLE) 8"x1(BASS)	1" x1 (TREBLE) 8"x1(BASS)