

**Professional Audio**
**KP-610**

- ▶ 10 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish


**KP-612**

- ▶ 12 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish


**KP-615**

- ▶ 15 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish



Model	KP-610	KP-612	KP-615
Frequency Response	60Hz-18KHz	60Hz-18KHz	60Hz-18KHz
Impedance	8	8	8
Rate Power	300W	400W	550W
Senistivity	95dB	95dB	95dB
Max SPL/1M	102dB	102dB	102dB
Size	300x340x524mm	350x382x600mm	430x430x680mm
Material	15mm Plywood, Aluminum frame	15mm Plywood, Aluminum frame	18mm Plywood, Aluminum frame
Configuration	34 coil 90 magnetic HF, 65 coin 156 magnetic LF	44 coil 120 magnetic HF, 75 coin 190 magnetic LF	44 coil 120 magnetic HF, 75 coin 190 magnetic LF

**PSRX712M**

- ▶ 12 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish


**PSRX715**

- ▶ 15 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish


**PSRX725**

- ▶ Dual 15 inch plywood speaker
- ▶ High power, reliable and performance
- ▶ Black painted finish



Model	PSRX712M	PSRX715	PSRX725
Power Rating/ Peak	300 W / 600 W	500W / 1000 W	1000 W / 2000 W
Frequency Range	70 Hz - 20kHz (-10 dB)	40 Hz - 20kHz (-10 dB)	37 Hz - 20kHz (-10 dB)
Dimensions (H x W x D)	349 mm x 546 mm x 260 mm (13.75 in x 21.5 in x 10.25 in)	711 mm x 439 mm x 406 mm (28 in x 17.3 in x 16 in)	1219 mm x 541 mm x 508 mm (48 in x 21.3 in x 20 in)
Frequency Response	83 Hz - 18 kHz (±3 dB)	53 Hz - 20 kHz (±3 dB)	53 Hz - 20 kHz (±3 dB)
Coverage Pattern	90° x 50° nominal	75° x 50° nominal	75° x 50° nominal
Net Weight	15 kg (33 lb)	22 kg (48 lb.)	45 kg (100 lb.)
Configuration	190 magnetic LF, 44 coil HF	100 coil 220 magnetic LF, 75 coil HF	100 coil 220 magnetic LF, 75 coil HF