

6 Zone Mixer Amplifier with Zone volume control



Mplayer A



Mplayer B



Mplayer C



Mplayer D

4 types of Media Player for you to choose to add to the Amplifier



Optional Mounts for assembly in 19 rack, Ordering code: RKM-01

Features:

► Controls

Front : 4 Input Channel Volume Control and 1 selectable source input Volume control,
Master Volume Control, 6 Zone Speaker Selector with 6 step attenuator.
Rear : Talkover Switch (VOX) & Phantom Power Switch for Channel 1-4. Chime enable with volume control.

Bypass contact input & system mute.

► Connectors

Input : Channel 1 - 4 : Electronically Balanced with chime switch.

Aux : Dual RCA.

Remote Mic : Rj45.

Emergency Alarm input : Euro block.

Output : Speaker Output : Euro Block . Attenuated and Switched 6 CH, Direct Output 4Ω, 70V, 100V.

REC Out & Link out : RCA.

Contact : Ext. Chime : Euro block.

MUTE : Euro block.

► Media player module : MPlayer A / MPlayer B / MPlayer C.

► Indicators : SIG, -10dB, CLIP & Protect. Zone selector.

► Protection : Output Current Limiting, Thermal Protection & DC Offset Protection.

► Cooling : Convection Cooling.

► Option : Rack Mount Kit.



MODEL	Mpro 130	Mpro 240	Mpro 360	Mpro 480	Mpro 600
Rated Power (RMS)	130W	240W	360W	480W	600W
Input sensitivity/ Impedance	Ch1-4 -45dB / -6dB Selectable / 20 kΩ Balanced				
	Aux 0dB / 20 kΩ Balanced				
	Remote Mic 0dB / 20 kΩ Balanced				
Output level/ Impedance	Hi-z 100V(83Ω),70V(42Ω)	100V(42Ω),70V(21Ω)	100V(28Ω),70V(14Ω)	100V(21Ω),70V(10Ω)	100V(16Ω),70V(8Ω)
	Low-z 22V (4Ω)	31V (4Ω)	38V (4Ω)	43V (4Ω)	48V (4Ω)
	Rec Out 0dB / 600Ω Unbalanced				
	Link Out 0dB / 600Ω Unbalanced				
Frequency Respose (-3dB)	65Hz - 18kHz				
T.H.D (1kHz, Rated Power)	<1%				
Signal to Noise Ratio	>80dB				
Tone Control (± 10dB)	100Hz , 10KHz				
Power Source	AC 115 / 230 V, 50/60Hz				
Weight (Net)	9 kg	10kg	11kg	12kg	13kg
Dimensions (W x H x D)	420 x88 x 320mm				