

SIP Control Station With Touch Screen

Description:

With a 10/100M Ethernet interface, line input and output, SIPM-30T is an SIP desktop intercom host that is used with SIP server. SIPM-30T network paging microphone can perform point-to-point IP intercom and multicast to the IP terminal through a microphone or local line input.

As a host of the IP broadcast intercom system, SIPM-30T can be used in places where intercom, monitor and emergency alarms are needed, such as control centers of self-service banks, interrogation rooms, classrooms, hospitals and parking lots.

As an intercom terminal, SIPM-30T supports full-duplex two-way intercom and has good echo suppression. We offer standard sip mode, which can be used in other standard SIP systems and compatible with standard SIP terminal devices.



Features:

- ▶ Stand-alone intercom function
- ▶ Stand-alone paging function
- ▶ Stand-alone unicast and multicast functions
- ▶ Support modify parameters directly on the mic
- ▶ Play Audio from SD or USB to the zones



Model	SIPM-30T
Network Communication Protocol	SIP
Network Interface	10/100Base-TX, RJ45
Frequency and Sampling Rate	8kHz-32 kHz, 16 bit
Decoding	MPEG,ADPC
Microphone Frequency Range	70Hz~12.5KHz
Operating Temp.	0~65° C
Screen	7" touch screen
Power Supply	DC 12V
Dimension	250 x 145 x 55 mm