

**270W Ferrite Unit Array Acoustic Column Speaker**

**Description**

Designed for small and medium-sized video conference rooms, digital courts, conference centers, lecture halls, lecture halls, other language-based sound reinforcement systems, and background music systems for various architectural spaces such as churches, museums, transportation hubs, and public areas in squares. This model solves a typical problem that the column speaker of the is too large to put on the wall, and it also looks not beautiful and tidy. Through the Constant Beam Technology in the line array sound column speaker, the problem of projection and interference of the traditional conference room speaker is solved. Therefore, in terms of sound performance, it is very good for the human sound reinforcement.



**Features**

- ▶ The array column loudspeaker adopts streamlined design with beautiful and practical appearance, which is suitable for sound reinforcement of various architectural spaces in superb sound quality.
- ▶ The sound column speaker is the fiberglass reinforced ABS cabinet, which is sturdy and durable.
- ▶ The circular waveguide hole in the front and the damping port at the rear of the box form a unique low-frequency cardioid diffusion. The treble is crisp and sweet, the sound is natural and thick, and the bass is full.

- ▶ 8\*3-inch high-performance Ferrite drive unit.
- ▶ ABS cabinet with UV resistant paint at IP55 rating is excellent for both outdoor and indoor applications

**Ordering Code:**

- LA-308LB V2: 270W@4OHM, Black
- LA-308B V2: 270W@4OHM, 100W@100V, 50W@70V, Switchable between music/speech modes, Black
- LA-308LW V2: 270W@4OHM, White
- LA-308W V2: 270W@4OHM, 100W@100V, 50W@70V, Switchable between music/speech modes, White

Model	LA-308LB V2/LA-308LW V2	LA-308B V2/LA-308W V2
Operating Modes	/	Switchable between music/speech mode
Input	4ohm	100V/70V/4ohm
Rated Power	270W@4ohm (1080W Peak)	270W@4ohm (1080W Peak) 100W/50W/25W/12.5W@100V 50W/25W/12.5W/6.2W@70V
Sensitivity (1m/1W)	93dB	
Max. SPL	124dB	
Frequency Range	100Hz~20kHz	
Cabinet Material	ABS plastic and fiberglass	
Mesh material	Aluminum	
Diffusion Angle (-6dB)	Vertical >30° , Horizontal >160°	
Installation	Intelligent mounting bracket or embedded mounting bracket	
Color	Black/White	
Dimension (H*W*D)	934x98x150mm	
Net Weight	4.85kg	
Speaker Driver	8x3" Ferrite	