

Garden Speaker

Ground Mounted Garden Speaker

- ▶ Weatherproof design for reliable outdoor use
- ▶ Sleek appearance with powerful sound performance
- ▶ With 15W transformer(Model with Suffix "T")

IP66



IP66



OD-515P

- ▶ Outdoor weatherproof garden speaker with high IP rating
- ▶ Present sound produced

IP66



OD-501P

- ▶ Outdoor high power speaker
- ▶ Radial design enable 360 degree sound dispersion
- ▶ Low frequency delivering depth sound

IP66



Model	GD-315T	GD-315L	GD-515T	GD-515L
Rated Power	15W@100V 7.5W@70V	15W@8ohm	15W@100V 7.5W@70V	15W@8ohm
Sensitivity	88±3dB	88±3dB	88±3dB	88dB±3dB
Freq. Response	100-18kHz	100-18kHz	100-18kHz	100-18kHz
Product Size	112x195x400mm	112x195x400mm	160x160x220mm	160x160x220mm
Installation	Ground Fix	Ground Fix	Ground Fix	Ground Fix
Material	Fiberglass	Fiberglass	Fiberglass	Fiberglass
IP Rating	IP66	IP66	IP66	IP66
Net Weight	1.1kg	1kg	2.2kg	2kg
Color	Black	Black	Sage Green	Sage Green
Speaker Driver	3" Full Range	3" Full Range	5.25" Full Range	5.25" Full Range

Model	OD-515P	OD-501P
Power at 100V	20/10W	30W
SPL(1W/1M)	95dB	95dB
Max SPL@ 1M	105dB	110dB
Freq. Response	80Hz-15KHz	100Hz-16KHz
Product Size	Dia 215x245mm	Dia 360x365mm
Installation	Ground fix	Ground fix
Enclosure Material	ABS	ABS
Weight	2Kg	3Kg
Color	Green	Sage Green
Speaker	5" x1 full range	4.5" x1 full range

Ground Mounted Garden Speaker

Features:

- ▶ Weatherproof design for reliable outdoor use
- ▶ Sleek appearance with powerful sound performance
- ▶ Support 100V/70V input

IP66



Model	GS-515TW	GS-515LW	GS-640TW	GS-640LW	GS-850FW	GS-850LW
Rated Power	15W@100V 7.5W@70V	15W@8ohm	40W/20W@100V 20W/10W@70V	40W@8ohm	50W/25W@100V 25W/12.5W@70V	50W@8ohm
Sensitivity	88±3dB	88dB±3dB	87dB±3	87dB±3	87dB±3	87dB±3
Freq. Response	100-18kHz	100-18kHz	100-18kHz	100-18kHz	100-18kHz	100-18kHz
Product Size	160x160x220mm	160x160x220mm	200x200x250mm	200x200x250mm	250x250x315mm	250x250x315mm
Installation	Ground Fix	Ground Fix	Ground Fix	Ground Fix	Ground Fix	Ground Fix
Material	Fiberglass	Fiberglass	Fiberglass	Fiberglass	Fiberglass	Fiberglass
IP Rating	IP66	IP66	IP66	IP66	IP66	IP66
Net Weight	2.2kg	2kg	3.3kg	3.1kg	5.7kg	5.5kg
Color	White	White	White	White	White	White
Speaker Driver	5.25" Full Range	5.25" Full Range	6.5" Coaxial	6.5" Coaxial	8" Full Range	8" Full Range