

3-Inch Ceiling Speaker

Features:

- With clear acoustic performance for music and voice
- Fast and easy installation feature



| Model | CP-303FM |
|-------------------------|---------------|
| Driver size | 3 inch |
| Rated Power | 1.5/3W |
| Sensitivity | 89dB±2(1W/1M) |
| Max SPL | 93dB |
| Speaker impedance | 8ohm |
| Frequency range | 100Hz-16KHz |
| 1000Hz Dispersion angel | 130 degree |
| Size | Φ120X80MM |
| Hole cut size | Φ100MM |
| Material | ABS |
| Color | White |

4-Inch Ceiling Speaker

Features:

- Elegant outlook.
- Easy to install and maintain.
- Made of durable material
- ABS enclosure
- IP64



Model with suffix "L" means Rimless

| Model | CP-406WP/CP-406WPL |
|--------------------|--------------------|
| Rated Power | 6W |
| Power Taps | 3/6W |
| Line Voltage | 100V |
| Sensitivity(1m,1W) | 91±3dB |
| Frequency Response | 150-18KHz |
| Dimension | Dia140x130mm |
| Hole for Mounting | Dia125mm |
| Material | ABS |
| Weight | 0.86kg |

Office Sound Masking Speaker

The SM-506 office sound masking speaker contains a 5.25-inch diameter speaker mounted on axis. The compact enclosure includes a convoluted, flame retardant, acoustical insert to eliminate standing waves and metallic resonance. It provides uniform dispersion and is well suited for sound masking, paging, and music signals.



Model

SM-506

| | |
|--------------------|------------------------------------|
| Power at 70V | 6W/3W/1.5W/0.75W/0.38W |
| Frequency Response | 100Hz-12KHz |
| Sensitivity | 83±3dB |
| Nominal Impedance | 100 V / Secondary Equals 8 Ohms |
| Nominal Dispersion | 160° H x 165° V |
| Height | 10.1cm |
| Weight | 1.6kg |
| Speaker | 5.25" full range paper cone driver |
| Color | White |

Ceiling Speaker

Features:

- Elegant outlook.
- Easy to install and maintain.
- Full range yet high quality music and speech reproduction
- ABS enclosure



Model with suffix "L" means Rimless



CSP-6T



CSP-6TL

| Model | CSP-6T | CSP-6 | CSP-6TL | CSP-6L |
|--------------------|--------------------|--------------------|--------------------|--------------------|
| Power at 100V | 3W/6W | / | 3W/6W | / |
| Power at 70V | 1.5W/3W | / | 1.5W/3W | / |
| Power at 8 ohm | / | 10W | / | 10W |
| SPL(1W/1M) | 92dB | 92dB | 92dB | 92dB |
| Max SPL@ 1M | 99dB | 101dB | 99dB | 101dB |
| Freq. Response | 100Hz-18KHz | 100Hz-18KHz | 100Hz-18KHz | 100Hz-18KHz |
| Cutout Size | Dia 165mm | Dia 165mm | Dia 165mm | Dia 165mm |
| Installation | Inceiling | Inceiling | Inceiling | Inceiling |
| Enclosure Material | ABS | ABS | ABS | ABS |
| Net Weight | 590g | 425g | 615g | 450g |
| Gross Weight | 705g | 540g | 730g | 570g |
| Color | White | White | White | White |
| Product Size | Dia187x65mm(H) | Dia187x65mm(H) | Dia189x65mm(H) | Dia189x65mm(H) |
| Package Size | 205x195x68mm | 205x195x68mm | 205x195x68mm | 205x195x68mm |
| Speakers | 6.5" x1 full range |