

Emergency Microphone Panel

Features:

- ▶ LED display screen with flash indicator to show the fire status
- ▶ 50 seconds message recording
- ▶ Manual / Auto trigger recorded message
- ▶ Vol control for handheld and PPT mic
- ▶ Short circuit try contact to activate emergency message



Model	EM-3
Audio Output	SIREN/Play/EMIC2 > or = to 8 mV, unbalanced
TRIG Output	Short Circuit signal activation output
Record Input	MIC >or= to 8 mV unbalanced, Line >or= 330mV unbalanced
Alarm Input	Short Circuit signal input
Alarm activation mode	Manual operation / alarm signal
Power Requirements	24VDC/500MA
Display	LCD Indicator
Power Consumption	Less than10W
Built-in Dimensions	2 U rack 19 inch
Net Weight	5 kg
Dimensions	89(H) x 483(W) x 366(D) mm

Programmable MP3 Timer

Features:

- ▶ With 4GB built-in memory, expandable to 8, 16 and 32GB
- ▶ 3.2 inch TFT true color display
- ▶ Support external U disc play
- ▶ Timing program via PC
- ▶ 4 sets of program, each up to 240 timings.
- ▶ With built-in FM function.
- ▶ With dry contact input to activate the built-in MSG.
- ▶ 1 MIC and 1 Aux inputs; 2 aux outputs.



Model with suffix "T" means touch screen version



Model	AS-TIME6/AS-TIME6T
Audio Output	10K ohms, less than 500mV unbalanced
Frequency Range	FM 87Mhz- 108Mhz
Antenna Input	75 ohms
THD	Less than 0.01% at 1kHz
S/N Ratio	Better than 80dB
Power Requirements	220-240V AC, 50/60 Hz;
Frequency Response	20Hz-18KHz
Power Consumption	10-15 W
Built-in Dimensions	2 U rack 19 inch