

Coaxial Ceiling Speaker Rimless Front with Safety Wire
Features

- ▶ Available in 6.5" and 8" coaxial ceiling speaker models.
- ▶ Selectable 100V / 70V / 8 Ω operation for flexible system integration.
- ▶ High sensitivity driving high SPL output.
- ▶ Wide dynamic response for speech and music reproduction.
- ▶ Front-access Phoenix terminal for easy wiring.
- ▶ Magnetic grille with high-strength N42 magnets.
- ▶ Etched metal grille with durable construction.
- ▶ Reinforced mounting structure with dual safety cables.
- ▶ Metal clamps for fast and secure ceiling installation.


DP660V2

DP8100V2

Model	DP660V2	DP8100V2
Power at 100V	5W/10W/20W/40W@100V, 60W@8 Ω	10W/20W/40W/80W@100V, 100W@8 Ω
Power at 70V	2.5W/5W/10W/20W@70V, 60W@8 Ω	5W/10W/20W/40W@70V, 100W@8 Ω
Power Peak	120W@8 Ω	200W@8 Ω
Speaker	1 × 6.5" + 1 × 1" Dome Tweeter (Coaxial)	1 × 8" + 1 × 1" Neodymium Tweeter (Coaxial)
Sensitivity (1m/1W)	90dB	92dB
Max. SPL@ 1M	110dB	115dB
Frequency Response	85Hz – 20kHz	65Hz – 20kHz
Coverage Angle	120° Conical	120° Conical
Grille Material	Metal	Metal
Back Cover Material	Iron	Iron
Mounting Clamp	Zinc Alloy	Zinc Alloy
Cutout Size	Dia 270mm	Dia 320mm
Product Size	Dia 316 × 197mm	Dia 375 × 258mm
Net Weight	3.9 kg	5.8kg